



Dear Sir or Madam:

Thank you for purchasing a Security Boss® Manufacturing, LLC., Cable Bite Guard. The Cable Bite Guard limits the kennel occupants' access to the lifting cable of the guillotine door, drastically reducing material and labor costs for replacing chewed cables. Please follow these directions for installing your new Cable Bite Guard.

Security Boss® Kennel Cable Bite Guards are intended to be installed over existing kennel rail systems. Mounting height of the Bite Guard varies by application. Mount so that bottom of bite guard covers the cable attachment to the kennel door. Be sure your existing kennel doors are installed and operating properly before installing the Cable Bite Guard.

Installing the Cable Bite Guard in wood, drywall, or masonry:

1. Position the Bite Guard so that the mounting flanges are on outside edges of the kennel rails. If installing in masonry, choose a mounting height that positions the mounting holes of the bite guard away from mortar joints
2. The height of the Cable Bite Guard on the wall should be determined by the height of the cable attachment to the guillotine door. Mount so that the bottom edge of the bite guard covers the cable attachment point of the kennel door.
3. Level the Cable Bite Guard and attach to the wood, drywall, or masonry using the appropriate fasteners. See image below for fastener locations:



4. Your Security Boss® Manufacturing Cable Bite Guard is now installed.

